



### Series 70S

#### Torque (Inch-Pounds)

Shutoff Pressure	2"	2 1/2"	3"	4"	5"	6"	8"	10"	12"
50psi	66	96	150	225	350	450	750	1325	2250
75psi	98	141	237	261	504	651	1050	1778	2990
100psi	103	148	249	343	531	685	1105	1872	3147
125psi	107	155	260	376	553	714	1151	1950	3279
150psi	110	158	265	384	564	728	1275	1989	3345
175psi	121	175	283	417	632	814	1337	2320	3923
200psi	132	192	300	450	700	900	1500	2650	4500
250psi	145	211	318	486	770	990	1695	2995	5085
285psi	160	232	337	528	847	1089	1915	3384	5746

### Series 70S

#### Cv

	2"	2 1/2"	3"	4"	5"	6"	8"	10"	12"
10°	2	3	8	17	47	91	116	223	303
20°	4	5	16	33	94	182	231	446	605
30°	8	11	23	57	143	248	330	633	825
40°	21	27	50	110	231	396	528	935	1320
50°	40	52	92	182	380	627	858	1320	2063
60°	87	121	147	297	578	902	1452	2090	3135
70°	108	172	224	462	908	1386	2508	3630	5528
80°	141	253	420	773	1485	2063	4158	6710	10230
90°	170	332	473	913	1650	2178	4257	7095	10780

### Flow Line Valve and Controls, LLC

110 Main Project Rd · Schriever, LA 70395 · Phone: 985-414-6000 · Toll Free 1-800-815-9226 · Fax 985-414-6072

[www.flowlinevalves.com](http://www.flowlinevalves.com)